


Fiber Optic Equipment

PG-150CMSC

Pigtail

Cable Type	Fiber Optic Pigtail SC/UPC
Color	Blue
Count Core	1 Core
Material	Flame PVC Outer Jacket
Mode	Single Mode
Temperature	-40°C~+70°C
Core Size	0.9 mm
Strip Size	1.5 M
Insertion Loss	0.28DB
Return Loss	55.8DB



FA-2SC-SC

Duplex Adapter

Cable Type	Fiber Optic SC to SC Adapter
Color	Blue
Count Core	2 Core
Material	Material Flame PVC Outer Jacket
Mode	Single Mode UPC Duplex Couplers
Temperature	-40°C~+70°C
Connector	SC Female to SC Female Fiber Coupler are Lightweight Due to Their Plastic
Ability	Fiber Optic Cable to Cable Connection or Patch Cords Extender in Local Area Networks (LANs), Wide Area Networks (WAN), Metropolitan Area Networks (MAN) Data Center, Business, Premises, Security, FTTH, FTTP, FTTA, High EMI, and Commercial Applications. SC-SC Fiber Adapter Duplex Comply with IEC 61754-4, IEC 60784-14 and TIA 604-3 and Conform to RoHS Standards



TC-60

Crimp

Cable Type	Termal Crimp
Color	White
Count Core	1 Core
Material	Flame PVC Outer Jacket
Mode	Single Mode, Multi mode
Heat Temperature	>125>
Core Size	60mm, Pin length: 55mm Inner
diameter	1.2mm
Reduced size	2.6mm

