

Patch Cord



PC-CM6UTP 50/100/200/300/500

Physical	
AWG	24
Termination	Rj45
Color	Yellow / Blue / Red / Gray / Green / Violet
Jacket	PVC- FR
Transmission Characteristics	
Type	Cat6 UTP
Mechanical Characteristics	
Maximum Pulling Force (E1-2-1-60794 IEC)	200N
Packaging	Individually Packaged in a Plastic Bag
Usage Characteristics	
Minimum Static Operating Bending Radius	10 mm
Operating Temperature, Range	-10 ~ 50°C
Meter	50 / 100 / 200 / 300 / 500 CM



PC-CM6SFTP 50/100/200/300/500

Construction Characteristics	
AWG	24
Termination	Rj45
Color	Yellow / Blue / Red / Gray / Green / Violet
Jacket	PVC- FR
Transmission Characteristics	
Type	Cat6 SFTP
Mechanical Characteristics	
Maximum Pulling Force (E1-2-1-60794 IEC)	200N
Packaging	Individually Packaged in a Plastic Bag
Usage Characteristics	
Minimum Static Operating Bending Radius	10 mm
Operating Temperature, Range	-10 ~ 50°C
Meter	50 / 100 / 200 / 300 / 500 CM

PF-SCLC / PF-SCSC / PF-LCLC 100/200/300

Patch cord	
Type	Single Mode Fiber
Termination	SC/LC - SC/SC - LC/LC
Color	Yellow
Jacket	PVC
Temperature	-40 °C ~ +60 °
Packaging	Individually Packaged in a Plastic Bag
Meter	100 / 200 / 300 CM

