

Socket

NS-3U 8P 6UTP

UTP Socket

Applicable Standards	T568A / T568B
Type	UTP - Cat6
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	3.4g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.1mm
Finished	0.3 Micro-Inch Gold Plating
Material	PVC



NS-3U 8P 6SFTP

SFTP Socket

Applicable Standards	T568A / T568B
Type	SFTP - Cat6
Contact Resistance	20 ohms
Insulation Resistance	100m ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	6.8g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.1mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal



NS-3U 8P 6SFTPS

SFTP Socket

Applicable Standards	T568A / T568B
Type	SFTP - Cat6
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	10.8g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.5mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal



NS-3U 8P 7SFTPS

SFTP Socket

Applicable Standards	T568A / T568B
Type	SFTP - Cat7
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	11.2g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	2.1mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal



NS-3U 8P 7SFTPSEO

SFTP Socket

Applicable Standards	T568A / T568B
Type	SFTP - Cat7 - End Open
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	11.2g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	2.1mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal



NS-3U 8P 6UTPEO

UTP Socket

Applicable Standards	T568A / T568B
Type	UTP - Cat6 - End Open
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	10.8g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.1mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC
Strain Relief	Metal



NS-3U 8P 6UTPTL

UTP Socket

Applicable Standards	T568A / T568B
Type	UTP - Cat6 - Toolless
Contact Resistance	20 ohms
Insulation Resistance	100 ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	19.2g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.5mm
Finished	0.3 Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal

